
Válvula de Globo ECO-VA40



GLOBE VALVE
METAL SEATED
Asbestos-Free
Straight Way pattern
PN 40
DN 15 - 200

APPLICATION

- Heating system with warm water and/or overheated water
- Low pressure steam system
- Heat transfer system
- Boiler equipment and/or pressure tank

OPERATING DATA

Temperature Max. = 400° C
Pressure Max. = 40 Bar
Rating indicated in table V-100898

DESIGN

Flange drilled and dimensioned DIN PN 40
Raised face flange DIN 2501
Face to Face length acc.to ISO
Note: The valves are in accordance with the safety requirement of appendix I of the 97/23/CE directive for fluid group 2

MATERIALS

- Body	Carbon Steel GS-C25
- Bonnet	Carbon Steel GS-C25
- Stem	Stainless Steel X 20 Cr 13
- Seat (cone)	Stainless Steel X 20 Cr 13(DN15-100)
	Stainless Steel X 20 Cr 13(DN125-200)
-Seat (body)	Stainless Steel X 10 CrNiTi 18.9
- Gasket	Graphite

ON ALL ORDERS PLEASE SPECIFY

GLOBE VALVE STRAIGHT WAY PATTERN
ECO-VA40 acc.to leaflet V-020699/2
PN 40 DN 15 - 200
Balancing cone standard DN 125-200

VARIANTS (Supplied upon request)

-Throttle cone, position indicator
-Stellitated seat, cone with ring P.T.F.E

DIMENSIONS mm

DN	V	L	D1	D2	D3	a	f	d	n	kg
15	170	130	95	65	47	16	2	14	4	4,0
20	195	150	105	75	58	18	2	14	4	5,3
25	200	160	115	85	68	18	2	14	4	5,7
32	235	180	140	100	78	18	2	18	4	10,0
40	275	200	150	110	88	18	3	18	4	13,3
50	275	230	165	125	102	20	3	18	4	15,3
65	345	290	185	145	122	22	3	18	8	25,2
80	355	310	200	160	133	24	3	18	8	32,2
100	415	350	235	190	162	24	3	22	8	50,5
125	490	400	270	220	184	26	3	26	8	78,0
150	545	480	300	250	218	28	3	26	8	104,0
200	680	600	375	320	280	34	3	30	12	198,0